

HAND-PULL VALVE



4H210-08



4H410-15

Ordering Code

4H

Specification Code
4H: 5/2(3) Way

2

Series Code
2: 200 Series
3: 300 Series
4: 400 Series

10

Motion Pattern
10: Single-head
Double-position
30: Single-head
Three-position

-

06

Port Size
06: G1/8"
08: G1/4"
10: G3/8"
15: G1/2"

-

L

Type Code
Blank: 5/3 Way Reset
Type
L: 5/3 Way Locking Type

Specification

Model	4H210-06	4H210-08	4H230-08	4H310-08	4H310-10	4H410-15
Working Medium	40 Micron Filtered Air					
Motion Pattern	Direct Drive Type					
Effective Section Area	14mm ² (CV=0.78)	16mm ² (CV=0.89)	12mm ² (CV=0.67)	25mm ² (CV=1.4)	30mm ² (CV=1.68)	50mm ² (CV=2.79)
Port Size	Air Inlet= Air Outlet= Exhaust=G1/8"	Air Inlet=Air Outlet=G1/4" Exhaust=G1/8"		Air Inlet= Air Outlet= Exhaust=G1/4"	Air Inlet= Air Outlet= = G1/8"	Air Inlet= Air Outlet= Exhaust = G1/2"
Working-pressure Range	0~0.8MPa					
Operating Temperature Range	0~60℃					