


KL0311 SERIES 4/2 WAY SOLENOID VALVE



Ordering Code

KL0311

Specification
Code

08

Port size
08: ZG1/4"
10: ZG3/8"
15: ZG1/2"

M5

Middle Port size
Blank: ZG1/8"
M5: M5

AC220V

Standard Voltage

DC12V

AC24V 50Hz/60Hz

AC110V 50Hz/60Hz

DC24V

AC220V 50Hz/60Hz

AC380V 50Hz/60Hz

Feature

Mainly used in air compressor to control loading, off-loading, pressurizing, decompression, inlet, exhaust automatically. It has the character of high pressure-proof, flexible acting, low demand of media purity because of piston construction and viton seal. It is 4/2 way solenoid valve (one inlet port, 2 working ports, one exhaust port). It is same with function of one 2/2 way (NC type) and one 3/2 way solenoid valve. It can reduced the cost of material and manufacturing, also can make the pipe line simple. this valve is with simple construction, small size, good sealing, easy fixing.

Specification

Model	KL0311
Orifice Size (mm)	Top: 2mm
	Body: 13mm
CV Value	3.6
Port Size	Top: ZG1/8"
	Middle: ZG1/8"、M5
	Body: ZG1/4"、ZG3/8"、ZG1/2"
Pressure Difference	0.05~1.2MPa
Temperature	-5~85℃
Voltage Tolerance	±10%
Body Material	Brass
Sealing Material	VITON or NBR

Overall Dimension

