

KLTJ SERIES ADJUSTABLE STEAM SOLENOID VALVE



Application

- ✓ Flow regulator. Widely used in steam, water, gas, liquid automatic control.
- ✓ It can be independently arranged on the ironing, ironing equipment.
- ✓ All of the heat resistant materials, high temperature reach to level H.
- ✓ It can control the flow of steam, convenient operation.
- ✓ The electrical part of waterproof, moisture-proof performance.

Technical Specification

Item	Description		
Port Size	ZG1/4"		
Orifice Size	2.0mm (to be customized)	2.7mm	3.0mm (to be customized)
Valve Material	Brass		
Seal	VITON		
Medium Temperature	-10℃~160℃		
Operating Pressure	0~1.0MPa		
Optional Voltage	12V/50; DC 12V; 24V/50; DC 24V; 110/120V/50; 220/230V/50		

XF SERIES 2/2 WAY PILOT ACTING SOLENOID VALVE



Application

- ✓ Widely used in water, gas, liquid automatic control.

Technical Specification

Item	Description		
Port Size	ZG1/4", ZG3/8", ZG1/2"		
Orifice Size	12mm		
Valve Material	Brass		
Seal	Rubber		
Medium Temperature	NBR: -5~80℃; EPDM: -5~120℃; VITON: -10~150℃		
Operating Pressure	0.05~1.0MPa		
Optional Voltage	12V/50; DC 12V; 24V/50; DC 24V; 110/120V/50; 220/230V/50		