

Q SERIES ELECTRIC SOLENOID VALVE



Q24DH-8



Q24D2H-8

Ordering Code

Q24 - D - H - 8

Series Code
Q Series 4/2
Way Pillar Type
Pneumatic
Change Valves


Control
D: Single Electric Control
D₂: Double Electric Control
Q: Single pneumatic
Control
Q₂: Double pneumatic
Control

Structure
Pillar
Type


Port Size
6: G1/8
(M10×1)
8: G1/4
(M12×1.25)
10: G3/8
(M16×1.5)
15: G1/2
(M20×1.5)

Graphic Symbol

Q24HD-□



Q24HD₂-□



Specification

Order Code	Q24HD-6	Q24HQ-6	Q24HD-8	Q24HQ-8	Q24HD-10	Q24HQ-10	Q24HD-15	Q24HQ-15
Parameter	Q24HD ₂ -6	Q24HQ ₂ -6	Q24HD ₂ -8	Q24HQ ₂ -8	Q24HD ₂ -10	Q24HQ ₂ -10	Q24HD ₂ -15	Q24HQ ₂ -15
Orifice Size (mm)	6		8		10		20	
Working Pressure (MPa)	0.2 ~ 0.8							
Turn-around Time (S)	0.1							
Ambient Temperature (°C)	-10 ~ 55							
Medium Temperature (°C)	0 ~ 55							
Power Voltage (V)	Electric Control AC: 220,110,36 DC: 48,24,12 Voltage hunting permission amounts to definite value +10%~-15% Gas to control does not have this parameter							
Life (Ten Thousand Times)	≥ 150							