

配件

线圈

PU线圈



KLS 线圈



4V210 线圈



KL0311 线圈



PU线圈

- ☑ 常规电压:
AC220V AC110V
DC24V DC12V
- ☑ 常规功率:
AC: 22VA DC: 13W
- ☑ 绝缘等级: H
- ☑ 线圈连接方式:
DIN43650A

KLS 线圈

- ☑ 常规电压:
AC220V AC110V
DC24V DC12V
- ☑ 常规功率:
AC: 17VA DC: 15W
- ☑ 绝缘等级: H
- ☑ 线圈连接方式:
DIN43650A

4V210 线圈

- ☑ 常规电压:
AC220V AC110V AC24V
DC24V DC12V
- ☑ 常规功率:
AC: 4.2~8.5V DC: 3~8W
- ☑ 绝缘等级: B、F、H
- ☑ 线圈连接方式:
DIN43650B

KL0311 线圈

- ☑ 常规电压:
AC220V AC110V
DC24V DC12V
- ☑ 常规功率:
AC: 15VA DC: 12W
- ☑ 绝缘等级: B、F、H
- ☑ 线圈连接方式:
DIN43650A

0927系列线圈



2W、2WB方线圈



2P025线圈



K2231~K5231系列线圈



0927系列线圈

- ☑ 线圈孔径、高度:
Φ13×41
- ☑ 适用功率及电压:
AC 15VA 12-380V
DC 12W 6-220V

2W、2WB方线圈

- ☑ 线圈孔径、高度:
Φ16×38
- ☑ 适用功率及电压:
AC 18VA 24-220V
DC 18W 12-220V

2P025线圈

- ☑ 线圈孔径、高度:
Φ9×29.5
- ☑ 适用功率及电压:
AC 8VA 12V-220V
DC 6W 6V-110V

K2231~K5231系列线圈

- ☑ 线圈孔径、高度:
Φ11.5×41
- ☑ 适用功率及电压:
AC 15VA 12-380V
DC 13W 12-220V