

K系列电控换向阀




K25D2-08

图形符号


K25HD-□




K25HD2-□



K25HK-□



K25HK2-□



订购码

K25H

系列代码
K系列二位五通
滑柱式气动换向阀

D

控制方式
D:单电控
D2双电控
K:单气控
K2:双气控

8

接管口径
6:1/8
8:1/4
10:3/8
15:1/2
20:3/4
25:1
32:1-1/4
40:1-1/2
50:2

AC220V

标准电压
DC24V
AC220V

G

牙型代码
G:G螺纹
ZG:ZG螺纹
NPT:NPT螺纹

规格

参 数	订货代号	K25HD-6 K25HD2-6 K25HK-6 K25HK2-6	K25HD-8 K25HD2-8 K25HK-8 K25HK2-8	K25HD-10 K25HD2-10 K25HK-10 K25HK2-10	K25HD-15 K25HD2-15 K25HK-15 K25HK2-15	K25HD-20 K25HD2-20 K25HK-20 K25HK2-20	K25HD-25 K25HD2-25 K25HK-25 K25HK2-25
工作压力		0.15~0.8					
介质温度		0~55					
环境温度		-5~50					
电源电压		AC : 220, 110, 36 ; DC : 24, 12 (气控无本项参数)					
寿命 万次		≥150					
工作介质		经净化、含有润滑油的压缩空气					
公称通径		6	8	10	15	20	25
流通能力S值		10	20	40	60	120	190
换向时间		≤0.06		≤0.08		≤0.12	
换向频率		≥10		≥8		≥5	
泄漏量		≤10		≤25		≤50	